NSN 5945-01-243-0784

Reed Relay - Page 1 of 2

8 tab, solder lug all functions



View Online at https://aerobasegroup.com/nsn/5945-01-243-0784

Overall Length:
0.800 inches
Overall Height:
0.340 inches
Overall Width:
0.285 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
End Application:
End item name: s3-96 ave tst
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.98 kilohms single winding and 2.53 kilohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.063 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, single throw, normally open, momentary action
Operating Voltage Rating And Type At Specificationified Temp:
24.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
$500.0 \ \text{milliamperes}$ ac resistive load and $500.0 \ \text{milliamperes}$ dc resistive load
Main Contact Maximum Voltage Rating In Volts:
130.0 ac and 100.0 dc
Energizing Element Power Rating:
270.0 milliwatts
Terminal Type And Quantity:

NSN 5945-01-243-0784

Reed Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300