# NSN 5945-01-243-4385

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-243-4385

Overall Length:
0.370 inches
Overall Height:
0.280 inches
Overall Width:
0.370 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.56 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 terminal single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized and coil voltage suppression
Cubic Measure:
0.038 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.004 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

## NSN 5945-01-243-4385

Electromagnetic Relay - Page 2 of 2



### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

### **Special Features:**

Failure rate level 0.1 percent

### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

8 wire lead all functions

#### **Specification Data:**

81349-mil-r-39016/18 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A03300