## NSN 5945-01-243-5621



Electromagnetic Relay - Page 1 of 2	A
View Online at https://aerobasegroup.com/nsn/5945-01-243-5621	
Overall Length:	
1.718 inches	
Center To Center Distance Between Mounting Facilities Parallel To Width:	
0.625 inches single mounting facility	
Overall Height:	
1.010 inches	
Overall Width:	
1.025 inches	
Mounting Slot Width:	
0.150 inches single mounting facility	
Case Material:	
Metal	
Environmental Protection:	
Hermetic	
Fragility Factor:	
Made retails were a	

Moderately rugged

**End Application:** 

Valve, reducin

**Winding Quantity:** 

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

Winding Dc Resistance Rating:

290.0 ohms single winding

**Duty Type:** 

Continuous

**Arc Quenching Method:** 

Air

**Mounting Facility Type And Quantity:** 

3 slotted hole single mounting facility

**Storage Type:** 

General purpose warehouse

**Cubic Measure:** 

1.778 cubic inches

**Mounting Facility Pattern:** 

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:** 

4 pole, double throw, one position momentary

**Operating Current Rating And Type:** 

120.0 milliamperes dc single winding

## NSN 5945-01-243-5621

Electromagnetic Relay - Page 2 of 2



Time Delay:
-------------

0.015 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.446 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Precious Material And Location:** 

Terminal surfaces gold

**Precious Material:** 

Gold

## **Test Data Document:**

81349-mil-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

14 pin all functions

**Specification Data:** 

96906-ms27400 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.