# NSN 5945-01-245-2265

Electromagnetic Relay - Page 1 of 2

0.850 inches single mounting facility

Overall Length: 1.062 inches

Overall Height: 0.320 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5945-01-245-2265

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

0.320 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.096 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
Specific
Coil Quantity:
1
Winding Dc Resistance Rating:
1.35 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.109 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.004 seconds fixed operate and release time

# NSN 5945-01-245-2265

Electromagnetic Relay - Page 2 of 2



Operating	Voltage	Rating	And '	Type At	Specif	icationified	Temp:
<b>- p</b> o. ag			,	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	O P O O		. Op.

26.5 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

## **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

## **Special Features:**

Failure rate level 0.1 percent

### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

8 wire lead all functions

### **Specification Data:**

81349-mil-r-39016/13 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300