

View Online at <https://aerobasegroup.com/nsn/5945-01-245-5422>

Overall Length:

2.187 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.844 inches single mounting facility

Overall Height:

2.166 inches

Overall Width:

1.031 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.147 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

Deception dev

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

4.884 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

70.0 milliamperes ac single winding

Time Delay:

0.05 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac inductive load and 2.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 pin all functions

Specification Data:

96906-ms25325 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.