NSN 5945-01-245-6275

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-245-6275

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 4.646 inches and 4.666 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.490 inches single mounting facility and 4.451 inches single mounting facility

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.865 inches single mounting facility and 3.885 inches single mounting facility

#### **Overall Height:**

Between 2.990 inches and 3.010 inches

**Overall Width:** 

Between 3.990 inches and 4.010 inches

**Case Material:** 

Metal

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.141 inches single mounting facility and 0.203 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

## **Winding Quantity:**

•

## **Purpose For Which Designed:**

General

## Coil Quantity:

1

### **Duty Type:**

Continuous

## **Arc Quenching Method:**

Air

#### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

## **Storage Type:**

General purpose warehouse

## **Cubic Measure:**

56.319 cubic inches

#### **Mounting Facility Pattern:**

Rectangular single mounting facility

## **Nonpile-up Main Contact Arrangement:**

1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

## Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 10.0 amperes dc resistive load

# NSN 5945-01-245-6275

Electromagnetic Relay - Page 2 of 2



## **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

6 threaded stud all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300