## NSN 5945-01-245-6493

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-245-6493

Overall Length:
0.880 inches
Overall Height:
0.490 inches
Overall Width:
0.480 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
End Application:
Csoc soc/ncs
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
7.5 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.207 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.005 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
6.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-245-6493

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

120.0 ac and 28.0 dc

**Precious Material And Location:** 

Contacts silver and contact surfaces gold

**Precious Material:** 

Gold and silver

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300