NSN 5945-01-245-9357

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-245-9357

1.980 inches Overall Height: 3.970 inches Overall Width: 1.980 inches Case Material: Plastic Environmental Protection: Dustproof Fragility Factor: Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Maximum Pated Voltage:	Overall Length:		
3.970 inches Overall Width: 1.980 inches Case Material: Plastic Environmental Protection: Dustproof Fragility Factor: Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	1.980 inches		
Overall Width: 1.980 inches Case Material: Plastic Environmental Protection: Dustproof Fragility Factor: Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Overall Height:		
1,980 inches Case Material: Plastic Environmental Protection: Dustproof Fragility Factor: Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	3.970 inches		
Case Material: Plastic Environmental Protection: Dustproof Fragility Factor: Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Overall Width:		
Plastic Environmental Protection: Dustproof Fragility Factor: Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	1.980 inches		
Environmental Protection: Dustproof Fragility Factor: Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Case Material:		
Dustproof Fragility Factor: Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Plastic		
Fragility Factor: Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Environmental Protection:		
Moderately rugged End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Dustproof		
End Application: Ssups Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Fragility Factor:		
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Moderately rugged		
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	End Application:		
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Ssups		
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Winding Quantity:		
General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	1		
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Purpose For Which Designed:		
Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	General		
Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Coil Quantity:		
Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	1		
Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Duty Type:		
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Continuous		
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Arc Quenching Method:		
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Air		
Storage Type: General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Mounting Facility Type And Quantity:		
General purpose warehouse Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	1 plug-in terminal single mounting facility		
Cubic Measure: 15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Storage Type:		
15.564 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	General purpose warehouse		
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Cubic Measure:		
2 pole, double throw, one position momentary Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	15.564 cubic inches		
Time Delay: 0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Nonpile-up Main Contact Arrangement:		
0.10 seconds adjustable release time and 3.00 seconds adjustable release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	2 pole, double throw, one position momentary		
Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding	Time Delay:		
24.0 volts dc 25 degrees celsius single winding	0.10 seconds adjustable release time and 3.00 seconds adjustable release time		
	Operating Voltage Rating And Type At Specificationified Temp:		
Main Contact Load Current Pating At Maximum Pated Voltage	24.0 volts dc 25 degrees celsius single winding		
Main Contact Load Current Rating At Maximum Rated Voltage.	Main Contact Load Current Rating At Maximum Rated Voltage:		
10.0 amperes ac resistive load and 10.0 amperes dc resistive load			
	Main Contact Maximum Voltage Rating In Volts:		
Main Contact Maximum Voltage Rating In Volts:	120.0 ac and 28.0 dc		
Main Contact Maximum Valtage Bating In Valtage			
	120.0 do dha 20.0 do		

Terminal Type And Quantity:

1 standard tube base all functions

NSN 5945-01-245-9357

Electromagnetic Relay - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300