

View Online at <https://aerobasegroup.com/nsn/5945-01-246-0377>

Overall Length:

3.730 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.240 inches single mounting facility and 3.260 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.677 inches single mounting facility and 2.697 inches single mounting facility

Overall Height:

Between 2.297 inches and 2.485 inches

Overall Width:

3.150 inches

Environmental Protection:

Dustproof and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.213 inches single mounting facility and 0.223 inches single mounting facility

Fragility Factor:

Moderately rugged

Frequency In Hertz:

60.0 or 400.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

200.0 milliamperes ac single winding

Time Delay:

0.05 seconds fixed release time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 50.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Terminal Type And Quantity:

12 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300