NSN 5945-01-246-7705

Electromagnetic Relay - Page 1 of 2

1.406 inches single mounting facility

Overall Length: 1.630 inches

Overall Height: 0.625 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5945-01-246-7705

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.075 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.120 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
6.84 kilohms single winding and 8.36 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.858 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.015 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts dc 25 degrees celsius single winding

NSN 5945-01-246-7705

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac inductive load and 6.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-r-5757/23 government specification

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A03300