NSN 5945-01-248-3456

Hybrid Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-248-3456

End Application: Oj-451 v 8 Contact Arrangement: Double pole, double throw Features Provided: Transistor driven and hermetically sealed Criticality Code Justification: Feat Special Features: Ifailure rate 3.0 pct; 1.0 amp resistive at 28 vdc; 200 ma at 28 vdc inductive; 100 ma at 28 vdc lamp; supply voltage 28 vdc; coil res 390 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
Contact Arrangement: Double pole, double throw Features Provided: Transistor driven and hermetically sealed Criticality Code Justification: Feat Special Features: 1 failure rate 3.0 pct; 1.0 amp resistive at 28 vdc; 200 ma at 28 vdc inductive; 100 ma at 28 vdc lamp; supply voltage 28 vdc; coil res 390 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
Double pole, double throw Features Provided: Transistor driven and hermetically sealed Criticality Code Justification: Feat Special Features: Ifailure rate 3.0 pct; 1.0 amp resistive at 28 vdc; 200 ma at 28 vdc inductive; 100 ma at 28 vdc lamp; supply voltage 28 vdc; coil res 390 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
Features Provided: Transistor driven and hermetically sealed Criticality Code Justification: Feat Special Features: 1 failure rate 3.0 pct; 1.0 amp resistive at 28 vdc; 200 ma at 28 vdc inductive; 100 ma at 28 vdc lamp; supply voltage 28 vdc; coil res 390 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
Transistor driven and hermetically sealed Criticality Code Justification: Feat Special Features: Ifailure rate 3.0 pct; 1.0 amp resistive at 28 vdc; 200 ma at 28 vdc inductive; 100 ma at 28 vdc lamp; supply voltage 28 vdc; coil res 390 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
Criticality Code Justification: Feat Special Features: Ifailure rate 3.0 pct; 1.0 amp resistive at 28 vdc; 200 ma at 28 vdc inductive; 100 ma at 28 vdc lamp; supply voltage 28 vdc; coil res 390 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
Feat Special Features: 1failure rate 3.0 pct; 1.0 amp resistive at 28 vdc; 200 ma at 28 vdc inductive; 100 ma at 28 vdc lamp; supply voltage 28 vdc; coil res 390 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
Special Features: 1 failure rate 3.0 pct; 1.0 amp resistive at 28 vdc; 200 ma at 28 vdc inductive; 100 ma at 28 vdc lamp; supply voltage 28 vdc; coil res 3 90 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
1failure rate 3.0 pct; 1.0 amp resistive at 28 vdc; 200 ma at 28 vdc inductive; 100 ma at 28 vdc lamp; supply voltage 28 vdc; coil res 390 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
390 ohms; electromechanical output; terminal mtd; 0.280 in. Lg; 0.370 in. Dia; moderately rugged; wt 2.60 grams Specification Data:	
Specification Data:	stance
04240 millio 2077C/A gavennesat and difference	
81349-mil-r-28776/1 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A513I0	