# NSN 5945-01-248-7090

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-248-7090

# Thread Class:

2a single mounting facility

#### **Thread Direction:**

Right-hand single mounting facility

#### **Overall Length:**

0.937 inches

#### **Overall Height:**

1.187 inches

#### **Overall Width:**

0.735 inches

#### Case Material:

Plastic

#### **Environmental Protection:**

Dustproof

#### Fragility Factor:

## Moderately rugged

Winding Quantity:

# 1

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

1

#### Winding Dc Resistance Rating:

485.0 ohms single winding

#### **Duty Type:**

Continuous

#### Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

#### Storage Type:

General purpose warehouse

#### **Cubic Measure:**

0.817 cubic inches

#### Thready Qty Per Inch (tpi):

48 single mounting facility

# Thread Size:

0.112 inches single mounting facility

# Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

# Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

# NSN 5945-01-248-7090

Electromagnetic Relay - Page 2 of 2



# Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac

# Thread Series Designator:

Unc single mounting facility

# Terminal Type And Quantity:

8 tab, solder lug all functions

## Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A03300