NSN 5945-01-249-0305

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-249-0305
Overall Length:
1.708 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.452 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.000 inches single mounting facility
Overall Height:
1.280 inches
Overall Width:
1.483 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
6625-01-187-3333
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:

Latching contacts and polarized

Cubic Measure:

3.242 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

NSN 5945-01-249-0305

Electromagnetic Relay - Page 2 of 2



Time D	elay:
--------	-------

0.015 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate is 3.0 percent per 10, 000 operations

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-r-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 pin all functions

Specification Data:

81349-mil-r-83536/26 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300