# NSN 5945-01-249-4767

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-249-4767

#### **Thread Class:**

2a single mounting facility

#### **Thread Direction:**

Right-hand single mounting facility

#### **Overall Length:**

1.156 inches

#### **Overall Height:**

1.531 inches

#### **Overall Width:**

0.910 inches

#### Case Material:

Plastic

#### **Environmental Protection:**

Dustproof

#### Fragility Factor:

#### Moderately rugged

## Winding Quantity:

### 1

**Purpose For Which Designed:** 

General

#### **Coil Quantity:**

1

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

## Storage Type:

General purpose warehouse

## Cubic Measure:

1.610 cubic inches

#### Thready Qty Per Inch (tpi):

48 single mounting facility

## Thread Size:

0.312 inches single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

## Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

 $3.0 \ \text{amperes} \ \text{ac} \ \text{resistive} \ \text{load} \ \text{and} \ 3.0 \ \text{amperes} \ \text{dc} \ \text{resistive} \ \text{load}$ 

NSN 5945-01-249-4767

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

**Thread Series Designator:** 

Unc single mounting facility

Terminal Type And Quantity:

8 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300