NSN 5945-01-251-4236

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-251-4236

Overall Length:
5.360 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.806 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.625 inches single mounting facility
Overall Height:
1.780 inches
Overall Width:
2.625 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.166 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
1440-01-087-9844
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
94.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility
4 unthreaded hole single mounting facility
4 unthreaded hole single mounting facility Pile-up Main Contact Form Arrangement:
4 unthreaded hole single mounting facility Pile-up Main Contact Form Arrangement: 52c
4 unthreaded hole single mounting facility Pile-up Main Contact Form Arrangement: 52c Storage Type:

Rectangular single mounting facility

Mounting Facility Pattern:

NSN 5945-01-251-4236

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Terminal Type And Quantity:

158 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300