NSN 5945-01-251-7961

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-251-7961

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Overall Length:
4.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.500 inches single mounting facility
Overall Height:
3.688 inches
Overall Width:
2.250 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.201 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Starter, motor
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
33.192 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, single throw, normally open, momentary action and 3 pole, single throw, normally closed, momentary action
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
3.500 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:

NSN 5945-01-251-7961

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Terminal Type And Quantity:

16 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300