## NSN 5945-01-251-8015

Electromagnetic Relay - Page 1 of 2



| Licetromagnetic relay 1 age 1 of 2                            | arvup |
|---|-------|
| View Online at https://aerobasegroup.com/nsn/5945-01-251-8015 |       |
| Thread Class:   |       |
| 2a single mounting facility                                   |       |
| Thread Direction:   |       |
| Right-hand single mounting facility                           |       |
| Overall Length:   |       |
| 1.172 inches  |       |
| Overall Height:   |       |
| 1.406 inches  |       |
| Overall Width:  |       |
| 0.735 inches  |       |
| Case Material:  |       |
| Plastic   |       |
| Environmental Protection:                                     |       |
| Dustproof   |       |
| Fragility Factor:   |       |
| Moderately rugged   |       |
| Winding Quantity:   |       |
| 1   |       |
| Purpose For Which Designed:                                   |       |
| General   |       |
| Coil Quantity:  |       |
| 1   |       |
| Winding Dc Resistance Rating:                                 |       |
| 2.5 kilohms single winding                                    |       |
| Duty Type:  |       |
| Continuous  |       |
| Arc Quenching Method:   |       |
| Air   |       |
| Mounting Facility Type And Quantity:                          |       |
| 1 threaded stud single mounting facility                      |       |
| Storage Type:   |       |
| General purpose warehouse                                     |       |
| Cubic Measure:  |       |

1.211 cubic inches

### Thready Qty Per Inch (tpi):

48 single mounting facility

#### Thread Size:

0.099 inches single mounting facility

### **Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

### **Operating Current Rating And Type:**

5.8 milliamperes dc single winding

# NSN 5945-01-251-8015

Electromagnetic Relay - Page 2 of 2



### Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

240.0 ac

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

14 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300