# NSN 5945-01-251-8016

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-251-8016

## **Overall Length:**

1.320 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.078 inches single mounting facility

#### **Overall Height:**

1.280 inches

#### **Overall Width:**

0.400 inches

#### **Mounting Slot Width:**

0.125 inches single mounting facility

#### **Case Material:**

Metal

**Environmental Protection:** 

#### Hermetic

Fragility Factor:

#### Moderately rugged

**Contact Material:** 

#### Silver

Winding Quantity:

1

**Purpose For Which Designed:** 

General

#### **Coil Quantity:**

1

## Winding Dc Resistance Rating:

200.0 ohms single winding

## Duty Type:

Continuous

## Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

## Storage Type:

General purpose warehouse

## Cubic Measure:

0.675 cubic inches

## Mounting Facility Pattern:

In-line single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

### Time Delay:

0.015 seconds fixed operate time

## NSN 5945-01-251-8016

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver

**Precious Material:** 

Silver

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300