NSN 5945-01-252-0203

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-252-0203

Overall Length:	
0.280 inches	

Overall Diameter:

Between 0.275 inches and 0.335 inches

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

125.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 terminal single mounting facility

Storage Type:

General purpose warehouse

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

200.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Special Features:

Failure rate 1.0 percent per 10000 cycles

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 wire lead all functions

Specification Data:

81349-mil-r-39016/7 government specification

Shelf Life:

N/a

NSN 5945-01-252-0203

Electromagnetic Relay - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

