NSN 5945-01-253-3800

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-253-3800

Overall Length:				
0.335 inches				
Overall Height:				
0.398 inches				
Overall Width:				
0.335 inches				
Case Material:				
Metal				
Environmental Protection:				
Hermetic				
Fragility Factor:				
Moderately rugged				
Winding Quantity:				
1				
Purpose For Which Designed:				
General				
Coil Quantity:				
1				
Winding Dc Resistance Rating:				
390.0 ohms single winding				
Duty Type:				
Continuous				
Arc Quenching Method:				
Air				
Mounting Facility Type And Quantity:				
1 terminal single mounting facility				
Storage Type:				
General purpose warehouse				
Cubic Measure:				
0.044 cubic inches				
Nonpile-up Main Contact Arrangement:				
2 pole, double throw, one position momentary				
Criticality Code Justification:				
Feat				
Time Delay:				
0.002 seconds fixed operate time				
Operating Voltage Rating And Type At Specificationified Temp:				
12.0 volts dc 25 degrees celsius single winding				
Main Contact Load Current Rating At Maximum Rated Voltage:				
100.0 milliamperes dc lamp load				
Main Contact Maximum Voltage Rating In Volts:				
115.0 ac and 28.0 dc				

NSN 5945-01-253-3800

Electromagnetic Relay - Page 2 of 2



_		_		
~n	ecial	I - 6	atıı	rae:

Failure rate level is 0.1 percent

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire lead all functions

Specification Data:

81349-mil-r-39016/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300