NSN 5945-01-254-2632

Electrical Solenoid - Page 1 of 2

17.00 pounds



View Online at https://aerobasegroup.com/nsn/5945-01-254-2632

Thread Class:
2a mounting facility stud
Thread Direction:
Right-hand mounting facility stud
Body Style:
Base end actuator
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.062 inches
Body Diameter:
1.562 inches
Body Height:
0.859 inches
Actuator Length:
0.750 inches
Fragility Factor:
Moderately rugged
Actuator Diameter:
0.218 inches
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
Magnetic Coil Quantity:
1
1 Electrical Resistance:
1 Electrical Resistance: 56.70 ohms
1 Electrical Resistance: 56.70 ohms Duty Type:
1 Electrical Resistance: 56.70 ohms Duty Type: Continuous
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location:
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating:
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 12.5 watts
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 12.5 watts Voltage Rating In Volts:
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 12.5 watts Voltage Rating In Volts: 27.0 dc
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 12.5 watts Voltage Rating In Volts: 27.0 dc Mounting Facility Type And Quantity:
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 12.5 watts Voltage Rating In Volts: 27.0 dc Mounting Facility Type And Quantity: 2 threaded stud
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 12.5 watts Voltage Rating In Volts: 27.0 dc Mounting Facility Type And Quantity: 2 threaded stud Storage Type:
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 12.5 watts Voltage Rating In Volts: 27.0 dc Mounting Facility Type And Quantity: 2 threaded stud Storage Type: General purpose warehouse
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 12.5 watts Voltage Rating In Volts: 27.0 dc Mounting Facility Type And Quantity: 2 threaded stud Storage Type: General purpose warehouse Thready Qty Per Inch (tpi):
Electrical Resistance: 56.70 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 12.5 watts Voltage Rating In Volts: 27.0 dc Mounting Facility Type And Quantity: 2 threaded stud Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 mounting facility stud

NSN 5945-01-254-2632

Electrical Solenoid - Page 2 of 2



Power Takeoff Connection Type:
Plain-drilled
Energizing Stroke Maximum Length:
0.020 inches
Thread Size:
0.138 inches mounting facility stud
Mounting Facility Pattern:
Two position in-line
Thread Series Designator:
Unc mounting facility stud
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A134a0