# NSN 5945-01-254-2633

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-254-2633

### **Thread Class:**

2a mounting facility stud

### **Thread Direction:**

Right-hand mounting facility stud

#### **Body Style:**

Double ended actuator

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches

#### **Body Diameter:**

1.562 inches

#### **Body Height:**

0.859 inches

#### Actuator Length:

0.500 inches and 0.750 inches

#### Fragility Factor:

Moderately rugged

## Actuator Diameter:

0.218 inches

## Inclosure Type:

Fully enclosed

## Magnetic Coil Quantity:

1

#### **Electrical Resistance:**

56.70 ohms

#### Duty Type:

Continuous

#### **Terminal Location:**

Circumference

#### **Electric Power Rating:**

12.5 watts

#### Voltage Rating In Volts:

27.0 dc

#### Mounting Facility Type And Quantity:

2 threaded stud

#### Storage Type:

General purpose warehouse

## Thready Qty Per Inch (tpi):

32 mounting facility stud

## Actuator Stroke Type:

Push

## Linear Force Delivered:

17.00 pounds

## NSN 5945-01-254-2633

Electrical Solenoid - Page 2 of 2



Power Takeoff Connection Type:

Plain-drilled

Energizing Stroke Maximum Length:

0.020 inches

Thread Size:

0.138 inches mounting facility stud

Mounting Facility Pattern:

Two position in-line

Thread Series Designator:

Unc mounting facility stud

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A134a0