# NSN 5945-01-254-4835

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-254-4835

## Overall Length:

2.312 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.188 inches single mounting facility

#### **Overall Height:**

5.062 inches

#### **Overall Width:**

2.000 inches

**Case Material:** 

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.180 inches single mounting facility

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.625 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

## End Application:

B-1bacftiate

#### D-IDacillate

Winding Quantity:

1

**Purpose For Which Designed:** 

General

#### **Coil Quantity:**

1

## Winding Dc Resistance Rating:

186.0 ohms single winding

#### Duty Type:

Continuous

## Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## Features Provided:

Wetted contact

#### Cubic Measure:

23.407 cubic inches

## Mounting Facility Pattern:

Diagonal single mounting facility

#### Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

## NSN 5945-01-254-4835

Electromagnetic Relay - Page 2 of 2



**Operating Current Rating And Type:** 120.0 milliamperes dc single winding Time Delay: 0.08 seconds fixed release time **Operating Voltage Rating And Type At Specificationified Temp:** 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 60.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 120.0 ac **Terminal Type And Quantity:** 4 screw all functions Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A03300