# NSN 5945-01-254-8177

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-254-8177

## **Overall Length:**

1.180 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.125 inches single mounting facility

### **Overall Height:**

0.580 inches

**Overall Width:** 

0.400 inches

Case Material:

Metal

**Environmental Protection:** 

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.096 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

### Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

700.0 ohms single winding

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## Cubic Measure:

0.274 cubic inches

## Mounting Facility Pattern:

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

## Criticality Code Justification:

Feat

## NSN 5945-01-254-8177

Electromagnetic Relay - Page 2 of 2



**Time Delay:** 

0.006 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

30.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Special Features:** 

Weapon system essential

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300