## NSN 5945-01-257-4019

Electromagnetic Relay - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

**Overall Length:** 

2a single mounting facility

Right-hand single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-01-257-4019

1.531 inches
Overall Height:
2.386 inches
Overall Width:
1.406 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
Winding Dc Resistance Rating: 1.7 kilohms single winding
1.7 kilohms single winding
1.7 kilohms single winding  Duty Type:
1.7 kilohms single winding  Duty Type:  Continuous
1.7 kilohms single winding  Duty Type:  Continuous  Arc Quenching Method:
1.7 kilohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air
1.7 kilohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:
1.7 kilohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:  1 threaded stud single mounting facility
1.7 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Storage Type:
1.7 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Storage Type: General purpose warehouse
1.7 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Storage Type: General purpose warehouse  Cubic Measure:
1.7 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 5.136 cubic inches
1.7 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 5.136 cubic inches  Thready Qty Per Inch (tpi):
1.7 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 5.136 cubic inches  Thready Qty Per Inch (tpi): 32 single mounting facility
1.7 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 5.136 cubic inches  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size:
1.7 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 5.136 cubic inches  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.138 inches single mounting facility

## NSN 5945-01-257-4019

Electromagnetic Relay - Page 2 of 2



Time Delay:
0.015 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes ac resistive load and 10.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
120.0 ac and 28.0 dc
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
11 quick disconnect, male all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A03300