NSN 5945-01-257-4020

Electromagnetic Relay - Page 1 of 2

240.0 volts ac 25 degrees celsius single winding



View Online at https://aerobasegroup.com/nsn/5945-01-257-4020

Overall Length:
6.438 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.625 inches single mounting facility
Overall Height:
4.594 inches
Overall Width:
3.313 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.120 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Starter motor
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
97.986 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, single throw, normally open, momentary action
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
5.625 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:

NSN 5945-01-257-4020

Electromagnetic Relay - Page 2 of 2



Main (Contact	Load	Curront	Dating	۸.	Maximum	Datad	Valtage:
IVIAIII (Joniaci	Loau	Current	Rauny	Αι	Maximum	Raieu	voitage.

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300