NSN 5945-01-258-7949

Electromagnetic Relay - Page 1 of 2

0.500 inches single mounting facility

Overall Length: 1.280 inches



View Online at https://aerobasegroup.com/nsn/5945-01-258-7949

Center To Center Distance Between Mounting Facilities Parallel To Width:

Overall Height:
0.820 inches
Overall Width:
0.810 inches
Mounting Slot Width:
0.133 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
4920-01-136-2857
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
400.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Cubic Measure:
0.850 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, double throw, one position momentary

NSN 5945-01-258-7949

Electromagnetic Relay - Page 2 of 2



Time Delay:

0.006 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.062 inches single mounting facility and 1.078 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

11 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300