NSN 5945-01-258-7950

Electromagnetic Relay - Page 1 of 2

Overall Length: 1.718 inches



View Online at https://aerobasegroup.com/nsn/5945-01-258-7950

Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches single mounting facility
Overall Height:
1.300 inches
Overall Width:
1.025 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
4920-01-136-2857
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
400.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Arc Quenching Method: Air
Air
Air Mounting Facility Type And Quantity:
Air Mounting Facility Type And Quantity: 3 slotted hole single mounting facility
Air Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Storage Type:
Air Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Storage Type: General purpose warehouse
Air Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Storage Type: General purpose warehouse Features Provided:
Air Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized
Air Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure:
Air Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 2.289 cubic inches
Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 2.289 cubic inches Mounting Facility Pattern:

NSN 5945-01-258-7950

Electromagnetic Relay - Page 2 of 2



Time Delay:

0.015 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac inductive load and 12.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

11 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300