# NSN 5945-01-258-7950

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-258-7950

## **Overall Length:**

1.718 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

### **Overall Height:**

1.300 inches

#### **Overall Width:**

1.025 inches

#### **Mounting Slot Width:**

0.150 inches single mounting facility

#### **Case Material:**

Metal

**Environmental Protection:** 

Hermetic

### Fragility Factor:

### Moderately rugged

End Application:

4920-01-136-2857

#### Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

## Winding Dc Resistance Rating:

400.0 ohms single winding

## Duty Type:

Continuous

## Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

## Storage Type:

General purpose warehouse

## Features Provided:

Polarized

## Cubic Measure:

2.289 cubic inches

## Mounting Facility Pattern:

Triangle single mounting facility

## Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

# NSN 5945-01-258-7950

Electromagnetic Relay - Page 2 of 2



#### **Time Delay:**

0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.396 inches single mounting facility and 1.446 inches single mounting facility **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 15.0 amperes ac inductive load and 12.0 amperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Terminal Type And Quantity:** 11 pin all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300