NSN 5945-01-259-9535

Electromagnetic Relay - Page 1 of 2

Overall Length: 1.718 inches



View Online at https://aerobasegroup.com/nsn/5945-01-259-9535

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility
Overall Height:
1.318 inches
Overall Width:
1.025 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
Keyline
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
2.321 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:
150.0 milliamperes dc single winding
Time Delay:
1.00 seconds adjustable release time and 10.00 seconds adjustable release time

NSN 5945-01-259-9535

Electromagnetic Relay - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

30.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300