# NSN 5945-01-260-5123

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-260-5123

• " "				
Overall Length:				
0.370 inches				
Overall Height:				
0.398 inches				
Overall Width:				
0.370 inches				
Case Material:				
Metal				
Environmental Protection:				
Dustproof				
Fragility Factor:				
Moderately rugged				
Winding Quantity:				
1				
Purpose For Which Designed:				
General				
Coil Quantity:				
1				
Winding Dc Resistance Rating:				
390.0 ohms single winding				
Duty Type:				
Continuous				
Arc Quenching Method:				
Air				
Mounting Facility Type And Quantity:				
1 terminal single mounting facility				
Storage Type:				
General purpose warehouse				
Cubic Measure:				
0.054 cubic inches				
Nonpile-up Main Contact Arrangement:				
2 pole, double throw, one position momentary				
Criticality Code Justification:				
Feat				
Time Delay:				
0.004 seconds fixed operate time				
Operating Voltage Rating And Type At Specificationified Temp:				
12.0 volts dc 25 degrees celsius single winding				
Main Contact Load Current Rating At Maximum Rated Voltage:				
500.0 milliamperes ac resistive load and 1.0 amperes dc resistive load				
Main Contact Maximum Voltage Rating In Volts:				

115.0 ac and 28.0 dc

## NSN 5945-01-260-5123

Electromagnetic Relay - Page 2 of 2



Char	.:	E	4	
Spec	Jiai	геа	tui	es.

Failure rate level 0.1 percent

#### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

8 wire lead all functions

### **Specification Data:**

81349-mil-r-39016/20 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300