

View Online at <https://aerobasegroup.com/nsn/5945-01-260-8499>

Overall Length:

1.062 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.850 inches single mounting facility

Overall Height:

0.320 inches

Overall Width:

0.310 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.096 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

Specific

Coil Quantity:

1

Winding Dc Resistance Rating:

56.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.105 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.004 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate level 0.1 percent

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire lead all functions

Specification Data:

81349-mil-r-39016/13 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300