## NSN 5945-01-261-0825

Electromagnetic Relay - Page 1 of 2

0.625 inches single mounting facility

Overall Length: 1.718 inches

Overall Height: 1.290 inches Overall Width: 1.025 inches

**Mounting Slot Width:** 



View Online at https://aerobasegroup.com/nsn/5945-01-261-0825

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
Lantirnnavpod
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
2.272 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Operating Current Rating And Type:
120.0 milliamperes dc single winding
Criticality Code Justification:
Feat

## NSN 5945-01-261-0825

Electromagnetic Relay - Page 2 of 2



## Time Delay:

0.015 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Special Features:** 

Failure rate level 0.3 percent

**Test Data Document:** 

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

14 pin all functions

**Specification Data:** 

96906-ms27400 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.