NSN 5945-01-262-0368

Electromagnetic Relay - Page 1 of 2

115.0 ac and 24.0 dc



View Online at https://aerobasegroup.com/nsn/5945-01-262-0368

| Overall Length: |
|---|
| 4.625 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.375 inches single mounting facility |
| Overall Height: |
| 6.250 inches |
| Overall Width: |
| 4.625 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.281 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| End Application: |
| Brake elec sh |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 133.691 cubic inches |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 25.0 amperes ac resistive load and 25.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |

NSN 5945-01-262-0368

Electromagnetic Relay - Page 2 of 2



| Terminal Type Ar | nd Quantity: |
|------------------|--------------|
|------------------|--------------|

10 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300