# NSN 5945-01-262-0396

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-262-0396

## **Overall Length:**

3.000 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility

#### **Overall Height:**

2.063 inches

**Overall Width:** 

3.000 inches

**Case Material:** 

Metal

**Environmental Protection:** 

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.156 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

## End Application:

5411-01-237-2786

### Frequency In Hertz:

400.0

### Winding Quantity:

1

# Purpose For Which Designed:

General

## **Coil Quantity:**

1

### Duty Type:

Continuous

### Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

# Storage Type:

General purpose warehouse

## Cubic Measure:

18.567 cubic inches

# Mounting Facility Pattern:

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

# NSN 5945-01-262-0396

Electromagnetic Relay - Page 2 of 2



Time Delay:

25.00 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
28.0 dc
Terminal Type And Quantity:
8 wire hook all functions
Shelf Life:
N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A03300