# NSN 5945-01-262-0398

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-262-0398

# **Overall Length:**

1.720 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.406 inches single mounting facility

### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

#### **Overall Height:**

1.738 inches

**Overall Width:** 

1.000 inches

#### Mounting Slot Width:

0.150 inches single mounting facility

**Case Material:** 

Metal

#### **Environmental Protection:**

Hermetic

#### **Fragility Factor:**

Moderately rugged

### End Application:

Radar cling

## Winding Quantity:

1

# Purpose For Which Designed:

General

# **Coil Quantity:**

1

# Winding Dc Resistance Rating:

150.0 ohms single winding

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

4 slotted hole single mounting facility

# Storage Type:

General purpose warehouse

# Cubic Measure:

2.989 cubic inches

# Mounting Facility Pattern:

Rectangular single mounting facility

# Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

# NSN 5945-01-262-0398

Electromagnetic Relay - Page 2 of 2



**Time Delay:** 

0.0075 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Terminal Type And Quantity:** 14 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300