# NSN 5945-01-262-9045

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-262-9045

## **Overall Length:**

1.718 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

#### **Overall Height:**

1.645 inches

#### **Overall Width:**

0.525 inches

#### **Mounting Slot Width:**

0.150 inches single mounting facility

#### **Case Material:**

Metal

**Environmental Protection:** 

Hermetic

#### Fragility Factor:

Moderately rugged

#### End Application:

Mk89mod1 gms

#### Winding Quantity:

1

**Purpose For Which Designed:** 

General

#### **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

320.0 ohms single winding

#### **Duty Type:**

Continuous

#### Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

#### Storage Type:

General purpose warehouse

#### Cubic Measure:

1.484 cubic inches

#### Mounting Facility Pattern:

In-line single mounting facility

## Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

#### Time Delay:

0.01 seconds fixed operate and release time

## NSN 5945-01-262-9045

Electromagnetic Relay - Page 2 of 2



#### Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

### Main Contact Maximum Voltage Rating In Volts:

115.0 ac

## Terminal Type And Quantity:

5 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300