NSN 5945-01-263-2808

Electromagnetic Relay - Page 1 of 2



Lieutionagnetic relay 1 age 1 of 2	arvup
View Online at https://aerobasegroup.com/nsn/5945-01-263-2808	
Overall Length:	
1.718 inches	
Center To Center Distance Between Mounting Facilities Parallel To Width:	
0.625 inches single mounting facility	
Overall Height:	
1.290 inches	
Overall Width:	
1.025 inches	
Mounting Slot Width:	
0.150 inches single mounting facility	
Case Material:	
Metal	
Environmental Protection:	
Hermetic	
Fragility Factor:	
Moderately rugged	
End Application:	
F-15e acft	
Frequency In Hertz:	
400.0	
Winding Quantity:	
1	
Purpose For Which Designed:	
General	
Coil Quantity:	
1	
Duty Type:	
Continuous	
Arc Quenching Method:	
Air	
Mounting Facility Type And Quantity:	
3 slotted hole single mounting facility	
Storage Type:	

Storage Type:

General purpose warehouse

Cubic Measure:

2.272 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

40.0 milliamperes dc single winding

NSN 5945-01-263-2808

Electromagnetic Relay - Page 2 of 2



Criticality Code Justification:
Feat
Time Delay:
0.05 seconds fixed release time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
115.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac lamp load and 2.0 amperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Failure rate level 0.3 percent
Test Data Document:
81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 pin all functions
Specification Data:
96906-ms27400 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300
Mil-std (military Standard):
Mil-r-6106 spec.