NSN 5945-01-263-9268

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-263-9268

Thread Class:

2b second mounting facility

Thread Direction:

Right-hand second mounting facility

Overall Length:

3.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches second mounting facility

Overall Height:

4.520 inches

Overall Width:

3.090 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.199 inches first mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches second mounting facility

Fragility Factor:

Moderately rugged

End Application:

Panel control

Frequency In Hertz:

60.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole first mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

45.392 cubic inches

NSN 5945-01-263-9268

Electromagnetic Relay - Page 2 of 2



Thready Qty Per Inch (tpi):
32 second mounting facility
Thread Size:
0.164 inches second mounting facility
Mounting Facility Pattern:
Rectangular second mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
1.00 minutes adjustable operate time and 10.00 minutes adjustable operate time
Nonpile-up Auxiliary Contact Arrangement:
1 pole, double throw, one position momentary
Auxiliary Contact Maximum Voltage Rating In Volts:
480.0 ac
Operating Voltage Rating And Type At Specificationified Temp:
110.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes ac resistive load and 15.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
240.0 ac and 30.0 dc
Auxiliary Contact Load Current Rating At Maximum Rated Voltage:
10.0 probe ac resistive load
Energizing Element Power Rating:
8.0 watts
Thread Series Designator:
Unc second mounting facility
Terminal Type And Quantity:
11 screw all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300