## NSN 5945-01-264-2822

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-264-2822

| Thread Class:                            |
|--|
| 2a single mounting facility              |
| Thread Direction:                        |
| Right-hand single mounting facility      |
| Overall Length:                          |
| 1.531 inches                             |
| Overall Height:                          |
| 2.250 inches                             |
| Overall Width:                           |
| 1.531 inches                             |
| Case Material:                           |
| Metal                                    |
| Environmental Protection:                |
| Hermetic                                 |
| Fragility Factor:                        |
| Moderately rugged                        |
| Contact Material:                        |
| Silver                                   |
| End Application:                         |
| Console systm                            |
| Frequency In Hertz:                      |
| 60.0                                     |
| Winding Quantity:                        |
| 1  |
| Purpose For Which Designed:              |
| General                                  |
| Coil Quantity:                           |
| 1  |
| Duty Type:                               |
| Continuous                               |
| Arc Quenching Method:                    |
| Air                                      |
| Mounting Facility Type And Quantity:     |
| 4 threaded stud single mounting facility |
| Storage Type:                            |
| General purpose warehouse                |
| Cubic Measure:                           |
| 5.274 cubic inches                       |
| Thready Qty Per Inch (tpi):              |
| 32 single mounting facility              |
| Thread Size:                             |
| 0.138 inches single mounting facility    |

## NSN 5945-01-264-2822

Electromagnetic Relay - Page 2 of 2



## **Mounting Facility Pattern:** Rectangular single mounting facility **Nonpile-up Main Contact Arrangement:** 4 pole, double throw, one position momentary Time Delay: 0.025 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac lamp load and 2.0 amperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver and terminal surfaces gold **Precious Material:** Gold and silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 14 pin all functions Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A03300