

View Online at <https://aerobasegroup.com/nsn/5945-01-265-1609>

Thread Class:

2a single mounting facility

Overall Length:

0.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.220 inches single mounting facility

Overall Height:

1.110 inches

Overall Width:

0.855 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.488 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

975.0 ohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Features Provided:

Latching contacts and polarized

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.005 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

150.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

10 wire hook all functions

Specification Data:

81349-mil-r-39016/32 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300