# NSN 5945-01-267-0813

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-267-0813

# **Overall Length:**

0.770 inches

**Overall Height:** 

0.290 inches

# Overall Width:

0.300 inches

# Case Material:

Plastic

# **Environmental Protection:**

Dustproof

Fragility Factor:

## Moderately rugged

Winding Quantity:

1

### Purpose For Which Designed:

#### General

**Coil Quantity:** 

1

### Winding Dc Resistance Rating:

450.0 ohms single winding

**Duty Type:** 

Continuous

### Mounting Facility Type And Quantity:

8 terminal single mounting facility

#### Storage Type:

General purpose warehouse

#### **Features Provided:**

Polarized and coil voltage suppression

#### Cubic Measure:

0.065 cubic inches

# Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

# Operating Voltage Rating And Type At Specificationified Temp:

5.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac resistive load

# Main Contact Maximum Voltage Rating In Volts:

100.0 dc

# **Energizing Element Power Rating:**

50.0 milliwatts

# Test Data Document:

81349-mil-r-83516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5945-01-267-0813

Reed Relay - Page 2 of 2



## Terminal Type And Quantity:

8 tab, solder lug all functions

### Specification Data:

81349-mil-r-83516/4 government specification

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A03300