## NSN 5945-01-267-0813

Reed Relay - Page 1 of 2

Overall Length: 0.770 inches Overall Height: 0.290 inches Overall Width: 0.300 inches Case Material:

Plastic



View Online at https://aerobasegroup.com/nsn/5945-01-267-0813

Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
450.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
8 terminal single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized and coil voltage suppression
Cubic Measure:
0.065 cubic inches
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Operating Voltage Rating And Type At Specificationified Temp:
5.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
500.0 milliamperes ac resistive load
Main Contact Maximum Voltage Rating In Volts:
100.0 dc
Energizing Element Power Rating:
50.0 milliwatts
Test Data Document:
81349-mil-r-83516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5945-01-267-0813

Reed Relay - Page 2 of 2



8 tab, solder lug all functions

**Specification Data:** 

81349-mil-r-83516/4 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A03300