NSN 5945-01-267-1054

Electromagnetic Relay - Page 1 of 2

Overall Length: 1.718 inches

Overall Height: 1.320 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5945-01-267-1054

Center To Center Distance Between Mounting Facilities Parallel To Length: 1.396 inches single mounting facility and 1.446 inches single mounting facility

| 0.525 inches |
|--|
| Mounting Slot Width: |
| 0.150 inches single mounting facility |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Fragility Factor: |
| Moderately rugged |
| End Application: |
| Vor and tacan |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 80.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 slotted hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Features Provided: |
| Polarized |
| Cubic Measure: |
| 1.191 cubic inches |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| |

NSN 5945-01-267-1054

Electromagnetic Relay - Page 2 of 2



| | Time | e De | elay: |
|--|------|------|-------|
|--|------|------|-------|

0.01 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300