## NSN 5945-01-268-6448

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-268-6448

| Overall Length:   |
|---|
| 0.370 inches  |
| Overall Height:   |
| 0.400 inches  |
| Overall Width:  |
| 0.370 inches  |
| Case Material:  |
| Metal   |
| Environmental Protection:                                     |
| Hermetic  |
| Fragility Factor:   |
| Moderately rugged   |
| End Application:  |
| 5895-01-252-7359  |
| Winding Quantity:   |
| 1   |
| Purpose For Which Designed:                                   |
| General   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:                                 |
| 200.0 ohms single winding                                     |
| Duty Type:  |
| Continuous  |
| Arc Quenching Method:   |
| Air   |
| Mounting Facility Type And Quantity:                          |
| 1 terminal single mounting facility                           |
| Storage Type:   |
| General purpose warehouse                                     |
| Features Provided:  |
| Polarized   |
| Cubic Measure:  |
| 0.055 cubic inches  |
| Nonpile-up Main Contact Arrangement:                          |
| 2 pole, double throw, one position momentary                  |
| Criticality Code Justification:                               |
| Feat  |
| Time Delay:   |
| 0.0075 seconds fixed release time                             |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 6.0 volts dc 25 degrees celsius single winding                |

## NSN 5945-01-268-6448

Electromagnetic Relay - Page 2 of 2



| Main   | Contact | l oad ( | Current | Rating | Δ+ N | Maximum      | Rated | Voltage: |
|--------|---------|---------|---------|--------|------|--------------|-------|----------|
| viaiii | Contact | LUau v  | Current | Naung  | AL I | VIAXIIIIUIII | naieu | voitage. |

100.0 milliamperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Energizing Element Power Rating:** 

60.0 milliwatts

**Special Features:** 

Failure rate level 0.1 percent

**Test Data Document:** 

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

8 wire lead all functions

**Specification Data:** 

81349-mil-r-39016/41 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300