NSN 5945-01-269-5992

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-269-5992

Overall Length:
2.660 inches
Overall Diameter:
1.140 inches
Case Material:
Metal and plastic
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.141 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Td set
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
290.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
2.715 cubic inches
Mounting Facility Pattern:
Ciruclar single mounting facility
· ·
Nonpile-up Main Contact Arrangement:
1 pole, double throw, one position momentary
Time Delay:
0.01 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
12.0 amperes ac resistive load and 12.0 amperes dc resistive load

NSN 5945-01-269-5992

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

9000.0 ac and 9000.0 dc

Test Data Document:

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 turret all functions

Specification Data:

81349-mil-r-83725/16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300