

View Online at <https://aerobasegroup.com/nsn/5945-01-269-7183>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

0.810 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.275 inches single mounting facility and 0.295 inches single mounting facility

Overall Height:

1.095 inches

Overall Width:

0.825 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.478 inches single mounting facility and 0.498 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

5820-01-231-4812

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

600.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.732 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.006 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300