NSN 5945-01-270-6089

Electromagnetic Relay - Page 1 of 2

25.0 amperes ac resistive load



View Online at https://aerobasegroup.com/nsn/5945-01-270-6089

| Overall Length: |
|--|
| 3.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility |
| Overall Height: |
| 4.250 inches |
| Overall Width: |
| 2.190 inches |
| Mounting Slot Width: |
| 0.210 inches single mounting facility |
| Case Material: |
| Plastic |
| Fragility Factor: |
| Moderately rugged |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 3 slotted hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 30.249 cubic inches |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 3.870 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 120.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |

NSN 5945-01-270-6089

Electromagnetic Relay - Page 2 of 2



| Main Contact Maximum Voltage Rating In Volts: |
|---|
| 240.0 ac |
| Terminal Type And Quantity: |
| 4 screw all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

No

Fiig:

A03300