NSN 5945-01-270-6089

Electromagnetic Relay - Page 1 of 2

25.0 amperes ac resistive load



View Online at https://aerobasegroup.com/nsn/5945-01-270-6089

Overall Length:
3.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches single mounting facility
Overall Height:
4.250 inches
Overall Width:
2.190 inches
Mounting Slot Width:
0.210 inches single mounting facility
Case Material:
Plastic
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
30.249 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
3.870 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:

NSN 5945-01-270-6089

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:
240.0 ac
Terminal Type And Quantity:
4 screw all functions
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A03300