NSN 5945-01-271-2118

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-01-271-2118 |
|---|
| Thread Class: |
| 2a single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 2.050 inches |
| Overall Height: |
| 1.250 inches |
| Overall Width: |
| 1.450 inches |
| Case Material: |
| Plastic |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Silver |
| Contact Surface Treatment: |
| Gold flash |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 472.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 1 threaded stud single mounting facility |
| Storage Type: |
| |

General purpose warehouse

Cubic Measure:

3.716 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

NSN 5945-01-271-2118

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load **Main Contact Maximum Voltage Rating In Volts:** 120.0 ac **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Silver and gold **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 8 tab, solder lug all functions Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No Fiig: A03300